Product data sheet

Specifications



Asfora - single socket outlet without earth - 16A cream

EPH3000123

IVI	a	ı	r	1
-----	---	---	---	---

Range	Asfora
Product or component type	Socket-outlet
Outlet poles configuration	2P
Device presentation	Complete product
Colour tint	Cream
Type of packing	Flow-pack

Complementary	
Socket number	1
Device mounting	Flush
Power range	3680 W
Rated current	16 A at 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm²
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 mm
Material	ABS (acrylonitrile butadiene-styrene): cover frame ABS + PC: central plate
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws5169 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	10 mm
Quantity per set	1
Net weight	0.072 kg

Environment

Standards	IEC 60884-1
Product certifications	SEP-BBJ TSE
IP degree of protection	IP20

Packing Units

r adming dimes	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	73.5 g
Package 1 Height	4 cm
Package 1 width	8 cm
Package 1 Length	8 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	813.0 g
Package 2 Height	9.5 cm
Package 2 width	18.5 cm
Package 2 Length	27.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Weight	10.38 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

Green Premium product	
REACh Declaration	
Compliant EU RoHS Declaration	
Yes	
Yes	
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Product Environmental Profile	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty 18 n	months
---------------	--------