

Product data sheet

Specifications



Asfora, SAT socket ending, 1dB, cream

EPH3700123

Main

Range	Asfora
Product or component type	SAT socket
Device presentation	Complete product
TV socket type	End-of-line (terminal socket)
Wiring device additional information	For series distribution systems For parallel distribution systems
Colour tint	Cream
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Socket number	1
SAT connector	F type
Attenuation	1 dB
DC current flow	In SAT socket
Number per line	1
Connections - terminals	Screwless terminals
Material	ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws 51...80 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	13 mm
Net weight	0.087 kg

Environment

Quality labels	CE
----------------	----

IP degree of protection	IP20
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	90.0 g
Package 1 Height	11 cm
Package 1 width	16 cm
Package 1 Length	5 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	1.039 kg
Package 2 Height	9.1 cm
Package 2 width	18.5 cm
Package 2 Length	27.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Weight	13.219 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------