Product data sheet

Specifications



Asfora - 2-way rotary dimmer - RC, 20-315VA white

EPH6600121

Range	Asfora
Product or component type	Dimmer
Device presentation	Complete product
Load type	230 V AC halogen lamp: 20315 W 230 V AC incandescent lamp: 20315 W Low voltage halogen lamp with electronic transformer: 20315 W
Colour tint	White
Type of packing	Вох

Complementary	
Device mounting	Flush
Switch function	1-pole 2-way
Dimmer control	Rotary push type
Dimmer application	Capacitive load Ohmic load
Protection type	Short-circuit and overload protection with automatic reset
[Ue] rated operational voltage	230 V AC 50 Hz
Connections - terminals	Pillar terminals
Number of cables	2 cable(s) 2.5 mm²
Cable stiffness	Flexible Rigid
Wire stripping length	8 mm
Material	ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame ABS (acrylonitrile butadiene-styrene): knob
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws5378 mm
Height	83 mm
Width	83 mm
Depth	49 mm
Projecting depth	20 mm

Net weight	0.111 kg
Environment	
Product certifications	VDE GOST SEMKO TSE NEMKO FIMKO UKR
Quality labels	CE
IP degree of protection	IP20
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	153.75 g
Package 1 Height	6.5 cm
Package 1 width	8.5 cm
Package 1 Length	8.5 cm
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Weight	3.928 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Offer Sustainability	
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

18 months

Contractual warranty

Warranty